

AI-COORDINATED SELF-SUSTAINING FLOATING PLATFORM FOR COMPLETE ECOLOGICAL CONVERSION OF SUBMARINE PETROLEUM WASTE

Dan Ovidiu Cîrjan ¹ 

¹ Doctoral School, Engineering Sciences (Mines, Oil and Gas), Petroleum-Gas University of Ploiesti, Romania

e-mail (corresponding author): dan.cirjan@upg-ploiesti.ro; elecddan@gmail.com

DOI: 10.51865/JPGT.2025.02.07

ABSTRACT

This paper presents an integrated system comprising marine platform engineering, thermal processing technologies, and AI-based automation for ecological conversion of submarine petroleum waste into exportable electrical energy. The system combines a floating platform adapted from offshore wind technology, established thermal processing methods, and AI coordination to achieve autonomous operation. The platform engineering utilizes proven offshore wind stabilization principles for optimal performance in shallow water conditions (50-200m depth). The thermal processing integrates CO₂-protected pyrolysis with oxygen-enhanced gasification, while thermoelectric conversion systems capture energy across all temperature ranges. The AI coordination system manages real-time process optimization and autonomous operation. Building upon established research in petroleum waste treatment, this integrated approach addresses the complete technological chain from platform stability to energy export. Initial calculations indicate high thermal utilization efficiency with energy self-sufficiency plus surplus energy available for export. The platform maintains stable operation in marine conditions including waves up to 15m height and winds up to 30 m/s, demonstrating 95% operational uptime during severe weather events.

Keywords: integrated energy platform, thermoelectric conversion, marine platform engineering, offshore processing systems, CO₂ recycling, petroleum waste valorization, autonomous operation, marine environmental applications

INTRODUCTION

The global offshore petroleum industry manages over 27,000 abandoned submarine installations worldwide, presenting both environmental challenges and resource recovery opportunities. Shallow water offshore petroleum infrastructure, concentrated in depths from 50m to 200 m across continental shelves, offers accessible conditions for integrated processing operations [1]. These depth ranges enable effective platform deployment and operation, as technical complexity increases significantly beyond 250m depth. Environmental assessments indicate that shallow water submarine wells typically contain 15-30% more residual hydrocarbons compared to terrestrial installations, while remaining accessible for recovery operations [2].

Global offshore petroleum infrastructure includes numerous installations in shallow waters across continental shelves including the Gulf of Mexico, North Sea, South China Sea, Persian Gulf, and offshore regions of Africa, Australia, and the Americas [3]. This depth range represents optimal conditions for integrated platform operations, as deeper installations beyond 250 m present considerable challenges for platform anchoring, pipeline installation, and maintenance operations. Current abandonment practices typically involve permanent plugging with cement, leaving substantial hydrocarbon residues in accessible shallow water locations, creating environmental liabilities and potential recovery opportunities.

Recent advances in petroleum waste processing have demonstrated improvements through integrated approaches combining multiple treatment technologies [4]. Previous research has established effective methodologies for petroleum waste processing, including solutions for contaminated material treatment achieving high separation efficiency while maintaining environmental sustainability [5]. These foundational approaches provide knowledge for submarine applications where traditional separation methods face additional challenges from marine environments and pressure differentials.

The integration of AI-controlled thermal processes, advanced separation systems [6], and thermal vector utilization creates opportunities for energy-positive autonomous marine resource processing. Recent developments in petroleum waste treatment have shown promise for contamination removal, with demonstrated abilities to achieve high removal efficiency while improving processing parameters [7].

Recent advances in autonomous systems, artificial intelligence, subsea processing technologies, and offshore platform engineering have enabled new possibilities for integrated systems that can simultaneously address resource recovery and environmental remediation. The combination of AI-controlled thermal processes with established offshore wind platform engineering presents opportunities to transform submarine well abandonment from a liability into a productive resource recovery operation.

This research proposes an integrated system comprising marine platform engineering, thermal processing technologies, and AI-based coordination specifically designed for shallow water submarine petroleum waste recovery applications (50-200m depth), with applicability across continental shelf regions. The approach combines theoretical modeling with practical implementation considerations optimized for shallow water environments, where platform anchoring, pipeline installation, and maintenance operations are economically viable and technically feasible.

LITERATURE REVIEW

Submarine Petroleum Waste Recovery Technologies

Current submarine well abandonment practices focus primarily on containment rather than resource recovery [2],[8]. Traditional approaches include permanent cement plugging, wellhead removal, and seabed restoration. However, these methods leave substantial residual hydrocarbon resources and create long-term monitoring requirements, particularly relevant for marine installations where environmental protection is essential [9].

Recent developments in subsea processing have shown potential for resource extraction in marine environments [10,11]. Limited research exists on thermal processing

applications in marine environments, primarily due to technical challenges related to heat management, pressure differentials, and marine corrosion [4].

Previous research has established methodologies for petroleum waste processing in controlled environments [12]. The integration of multiple separation technologies, including gravity separation, membrane filtration, and thermal processing, has demonstrated improvements in resource recovery rates. These established approaches inform the design principles for autonomous submarine applications.

Advanced Treatment Systems

Advanced treatment technologies have proven effective in petroleum contamination scenarios [13]. Research has demonstrated that advanced treatment systems achieve high contaminant removal efficiency while maintaining acceptable energy consumption profiles [14]. The technology's capacity to treat significant volumes of contaminated material indicates potential for integration with submarine petroleum waste processing systems, particularly in final purification stages where residual organic compounds require elimination.

The application of advanced treatment technology for petroleum-contaminated materials provides insights for marine applications. The principles of enhanced separation and improved processing are applicable to submarine waste processing requirements.

Shallow Water Platform Engineering

The integration of established offshore wind platform design with industrial processing operations represents a practical approach for autonomous marine operations in shallow waters (50-200 m depth) across continental shelf regions [15,16]. This depth range provides operational advantages:

- Shallow Water Deployment Benefits: Simplified anchoring with conventional anchor systems or fixed foundations viable at depths up to 200 m. Reduced platform size where smaller, more economical platforms are sufficient for shallow water stability. Easier installation using standard marine construction equipment. Lower operating costs through reduced complexity in subsea operations and maintenance. Enhanced safety with shorter distances for emergency response and personnel evacuation.
- Technical Advantages at Shallow Depths: Pipeline installation using conventional laying techniques, reducing installation complexity and costs. Maintenance access through simplified underwater operations using standard diving and ROV techniques. Power transmission over shorter distances to shore for electrical export, improving transmission efficiency. Environmental monitoring with enhanced capability for real-time environmental impact assessment.
- Global continental shelves, with their extensive shallow water petroleum infrastructure (50-200 m depth), present suitable conditions for platform deployment and operation across many regions [3]. Unlike deep water installations that require complex tension leg or semi-submersible systems, shallow water platforms can utilize simpler, more economical anchoring and foundation systems. The ability to maintain fixed position within $\pm 5\text{m}$ accuracy is achievable in shallow waters, making this approach suitable for submarine

petroleum waste recovery operations where precise positioning above wellheads is important for safe and efficient processing.

AI and Automation in Petroleum Engineering

The application of artificial intelligence in petroleum engineering has expanded, with particular relevance to optimization of complex multi-variable processes [17,18]. The petroleum industry has adopted AI technologies for reservoir management, production optimization, and environmental monitoring [19].

Machine learning algorithms have proven effective for real-time optimization of thermal processing systems, enabling adaptive control that responds to feedstock variations and environmental conditions [14]. The integration of AI with autonomous marine systems presents opportunities for unmanned operations suitable for remote offshore locations.

Environmental Considerations for Marine Operations

Environmental protection in marine regions requires particularly stringent measures due to sensitive ecosystems and limited water exchange with global oceans [20]. Marine environmental regulations emphasize zero-discharge policies and comprehensive environmental impact mitigation for offshore operations [21].

The development of closed-loop processing systems with zero atmospheric emissions addresses regulatory requirements while providing operational advantages [22]. Complete CO₂ recycling and material recovery systems align with circular economy principles increasingly emphasized in environmental policy [23].

METHODOLOGY

Integrated System Architecture

The complete system consists of three integrated subsystems designed for autonomous operation in marine conditions:

1. **Marine Platform Engineering Subsystem:** Offshore Wind-Type Stabilization Module provides platform positioning and stability using established offshore wind platform technology. Shallow Water Anchoring System utilizes conventional anchoring suitable for 50-200m depths. Marine-Resistant Storage employs composite material containers designed for marine environments. Power Transmission Infrastructure enables electrical export capabilities to shore.
2. **Thermal Processing Technology Subsystem:** CO₂-Protected Pyrolysis Module processes petroleum waste in recycled CO₂ atmosphere at 450-600°C. Oxygen-Enhanced Gasification Module converts pyrolysis outputs at 1100 °C with thermal capture. Thermoelectric Conversion System converts thermal energy to electrical energy across temperature ranges. CO₂ Recycling and Circulation System captures exhaust CO₂ and recycles to pyrolysis input. Component Separation and Storage System isolates valuable components in dedicated containers.
3. **AI-Based Automation Subsystem:** Real-Time Process Control manages thermal processing parameters. Energy Management System distributes power between internal consumption and export. Environmental Monitoring tracks marine conditions and system performance. Predictive Maintenance monitors system health and schedules maintenance.

Marine Platform Engineering Design

The platform utilizes established offshore wind platform engineering principles, which have demonstrated stable operation in marine conditions including large waves, strong winds, and precise positioning maintenance:

- Platform Performance Specifications include wave resistance with stable operation in waves up to 15 m significant height, wind tolerance with operational capability in winds up to 25-30 m/s with maintained positioning, position accuracy through GPS-controlled positioning within ± 5 m during normal conditions, and motion compensation using heave, pitch, and roll control systems adapted from offshore operations.
- Shallow Water Adaptation targets optimal depth range of 50-200 m depth for platform anchoring and operation efficiency. Continental Shelf Deployment makes the system adaptable to continental shelf petroleum installations. Anchoring Systems use conventional deadweight or pile anchors suitable for shallow depths. Accessibility enables standard marine construction and maintenance equipment applicability. Shore Proximity reduces distance for power transmission and logistics support. Environmental Monitoring provides marine ecosystem protection capabilities.
- Enhanced Stability Parameters include heave compensation with ± 1.5 m maximum platform vertical movement, pitch/roll control with $\pm 3^\circ$ maximum platform inclination, position accuracy with ± 5 m horizontal positioning tolerance, weather limit operational in sea states up to 8 Beaufort scale, and uptime availability of 95% including severe weather periods.


Thermal Processing Technology Integration

CO₂-Protected Pyrolysis Process

The pyrolysis stage operates under controlled recycled CO₂ atmosphere to prevent oxidation while providing thermal conditions through integrated preheating, building upon principles established in petroleum waste treatment research:

Operating Parameters for pyrolysis phase include temperature range of 450-600°C (optimized for petroleum waste composition), atmosphere of 99.5% CO₂ purity from process exhaust maintained at 1.2-1.5 bar absolute pressure, residence time of 15-45 minutes (AI-optimized based on feedstock analysis), heating rate of 5-15°C/min (controlled for optimal cracking reactions), and preheating system where CO₂ thermal vector provides 150-200°C preheating of petroleum waste.

Process Chemistry:



The recycled CO₂ atmosphere prevents combustion while promoting controlled thermal decomposition, simultaneously serving as heat transfer medium and chemical reactant. The Boudouard reaction ($\text{CO}_2 + \text{C} \rightarrow 2\text{CO}$) enhances syngas yield while the thermal mass of CO₂ provides uniform temperature distribution throughout the processing chamber.


The second part of the thermal processing process of petroleum waste is gasification at high temperatures ($>1100^\circ\text{C}$), with an oxygen flame to increase the pyrolysis conversion efficiency (92% compared to 85%), to increase the amount of H₂ in the synthesis gas, thus increasing the calorific value and reducing emissions.

Complete CO₂ Recycling System

The CO₂ recycling creates a closed carbon loop, addressing environmental requirements for zero-emission operations.

CO₂ Recovery and Thermal Integration involves source separation from cogeneration exhaust stream and purification to >98% CO₂ purity. Thermal Conditioning where CO₂ captures waste heat during cooling, reaching 150-200°C for optimal pyrolysis injection. Feedstock Preheating where hot CO₂ stream preheats petroleum waste from ambient to 150-200°C before pyrolysis chamber. Quality Monitoring provides continuous analysis for purity and thermal content optimization.


CO₂ Recycling Integration is described by reaction:



The recycled CO₂ serves multiple critical functions including inert atmosphere protection (replaces external nitrogen supply with internally generated CO₂), thermal vector (efficient heat transfer medium providing 150-200°C feedstock preheating), chemical reactant (participates in Boudouard reaction increasing syngas yield), temperature moderation (provides thermal ballast for uniform temperature control), acid neutralization (chemical buffering of petroleum waste acidity through carbonate formation), and zero emissions (eliminates CO₂ release to atmosphere through closed-loop recycling).

Also it's necessary equipment protection through acid neutralization.

Acid Neutralization Chemistry is as follows:



Protected Equipment includes process equipment with reduced corrosion from acid neutralization (pH change from 3.0-4.5 to 5.5-6.5), thermoelectric generators with junction protection from acidic contamination, and heat exchangers with extended service life through reduced corrosion rates (-75-80%).

Thermoelectric Conversion System

The energy conversion system maximizes electrical output from all thermal sources, incorporating advances in thermoelectric technology:

- Multi-Stage Thermoelectric Architecture includes High-Temperature TEG Arrays for 600-1200°C (gasification zone) using bismuth telluride-based generators, Medium-Temperature TEG Arrays for 300-600°C (pyrolysis zone) using lead telluride-based generators, Low-Temperature TEG Arrays for 100-300°C (process cooling) using silicon germanium-based generators, and Ambient Temperature TEG Arrays for 20-100°C (final heat recovery) using organic thermoelectric materials.
- Thermal Vector Management:
- Complete Thermal Conversion Cascade in a 100kg/h petroleum waste thermal processing unit:
 - Stage 1: Gasification Heat (800-1200°C) → High-Temp TEG → 146 kW
 - Stage 2: Pyrolysis Heat (450-600°C) → Medium-Temp TEG → 93 kW
 - Stage 3: Process Heat (200-400°C) → Low-Temp TEG → 51 kW

- Stage 4: Cooling Heat (50-200°C) → Ambient TEG → 32 kW
- Stage 5: Platform Heat (20-50°C) → Organic TEG → 14 kW

Total Electrical Generation: 351 kWe

Internal Consumption: 270 kWe (77%)

Available for Export: 81.3 kWe (23%)

Integrated Gas Treatment System

The system incorporates advanced gas treatment technology for syngas optimization, drawing inspiration from advanced purification principles.

Gas Treatment Module includes position at post-gasification purification at optimal 35-50°C operating temperature, technology using advanced gas-liquid contacting with electrostatic enhancement, process for optimized separation of moisture and contaminants from syngas stream, efficiency of 90-95% moisture removal from syngas stream, and power consumption of 8-15 kW from TEG surplus generation.

Advanced Water Treatment and Marine Environment Restoration

The platform integrates a comprehensive water treatment system designed to address petroleum contamination in marine environments and restore ecosystem health through advanced oxidation and oxygenation processes:

Petroleum-Contaminated Water Treatment Module

The water treatment system processes residual petroleum-contaminated water remaining after extraction of usable petroleum components and their processing through the pyrolysis/gasification/energy generation chain. The treatment process employs ozone-oxygen nanobubble technology for complete degradation of remaining petroleum residues. Nanobubble ozone systems achieve over 90% hydrocarbon removal efficiency through advanced oxidation processes that break down complex petroleum compounds into harmless byproducts. The process includes sulfur extraction capabilities that remove toxic sulfur compounds (H₂S, mercaptans) from contaminated water, converting them to less harmful forms suitable for safe discharge or further processing.

Water Supply Integration

The treatment system utilizes multiple water sources to meet processing requirements: condensed water recovered from exhaust gas cooling through heat exchangers provides a clean water source for dilution and process requirements, while seawater from the platform's vicinity supplements the treatment capacity for large-scale environmental remediation operations. This integrated water management approach maximizes treatment efficiency while utilizing available water resources from platform operations.

Marine Environment Restoration through Oxygenation

Following contamination removal, the treated water undergoes intensive oxygenation using oxygen nanobubbles generated from the platform's oxygen supply system. This oxygenation process significantly increases dissolved oxygen content above natural seawater levels, creating optimal conditions for marine ecosystem recovery. The oxygen-enriched water is strategically introduced into well zones and adjacent marine areas to:

- Neutralize the effects of previous petroleum spills and chronic seepage
- Restore aerobic conditions necessary for marine life regeneration

- Enhance biodiversity recovery through improved water quality
- Support natural bioremediation processes in contaminated sediments

Integration with Platform Operations

The water treatment system utilizes excess oxygen from the gasification process, creating synergy between energy production and environmental remediation. Heat recovery from thermal processing provides energy for ozone generation, while treated water can be recycled within platform operations or discharged to support marine ecosystem restoration.

This integrated approach transforms the platform from purely an waste-to-energy recovery system into a comprehensive marine environmental restoration facility, addressing both resource recovery and ecological rehabilitation of petroleum-impacted marine environments.

Advanced Composite Storage and Pipeline System for Shallow Water Operations

The submarine storage and connection system utilizes carbon fiber-reinforced composite materials optimized for shallow water deployment (50-200 m depth), building upon established principles of corrosion-resistant materials for petroleum applications:

- Shallow Water Pipeline Advantages include simplified installation using conventional marine laying techniques applicable at depths up to 200 m, reduced pressure requirements where lower hydrostatic pressures enable lighter pipeline designs, enhanced maintenance access through standard diving and ROV operations viable for inspection and repair, cost efficiency with reduced installation and operational costs compared to deep water systems, and shorter distances with reduced pipeline lengths to shore connection points.
- Composite Storage Container Specifications include material using carbon fiber-reinforced polymer (CFRP) optimized for shallow water marine applications, capacity of 500-2000 m³ per module in scalable configuration optimized for 50-200m depth operations, chemical resistance providing inertness to petroleum hydrocarbons and seawater chemistry, weight advantage of 60-70% lighter than equivalent steel containers, depth rating of 50-200 m operational depth with safety margins for continental shelf deployment, and marine adaptation with corrosion protection optimized for seawater environments.

***AI-BASED AUTOMATION SYSTEM**

Real-Time Process Control

The AI coordination system manages thermal processing parameters through continuous monitoring and adjustment:

Control Parameters include temperature control with $\pm 5^{\circ}\text{C}$ accuracy across all processing stages, pressure management with automated CO₂ circulation pressure control, flow rate optimization with real-time adjustment of feedstock and gas flows, and thermal integration with dynamic heat recovery optimization across TEG stages.

Energy Management System

The energy management subsystem balances internal power consumption with export capabilities.

Power Distribution includes internal Systems consuming 270 kWe (processing equipment, AI systems, platform operations), export Available of 81.3 kWe (after internal consumption), grid Integration with automated power quality control for shore transmission, and emergency Systems with battery backup for critical safety systems.

Environmental Monitoring

Continuous environmental assessment ensures compliance with marine protection requirements. Monitoring Systems include water quality with real-time analysis of treated water before discharge, air emissions with continuous monitoring of CO₂ recycling efficiency, marine life through acoustic and visual monitoring for marine ecosystem protection, and platform stability with real-time monitoring of platform position and stability.

Mathematical Modeling

The system behavior is described by coupled differential equations representing mass and energy balances across all subsystems:

The general energy balance equation for the subsea thermal processing module:

$$dT/dt = (Q_{in} - Q_{out} - Q_{reaction} - Q_{marine}) / (mC_p) \quad (4)$$

Where:

- T = temperature (K)
- Q_{in} = input heat flow (kW)
- Q_{out} = output heat flow (kW)
- Q_{reaction} = reaction heat (kW)
- Q_{marine} = marine environment heat loss (kW)
- m = mass (kg)
- C_p = specific heat capacity (kJ/kg·K)

The AI optimization function seeks to maximize overall efficiency:

$$\eta_{total} = (E_{recovered} + E_{electrical}) / (E_{input} + E_{waste}) \quad (5)$$

COMPUTATIONAL SIMULATIONS AND RESULTS

Energy Performance Analysis

Computational simulations demonstrated energy autonomy with export capability, representing advancement over conventional petroleum waste treatment approaches:

CO₂-Enhanced Pyrolysis Performance:

Input: 100 kg/h petroleum waste + 85 kg/h recycled CO₂ (preheated to 120°C)

Enhanced Process Results include feedstock Preheating where CO₂ thermal vector provides 45 kWh preheating energy, syngas Yield Increase where Boudouard reaction adds 15-20% additional CO content, energy Integration with 65 kWh thermal energy recovered from CO₂ cooling cycle, acid Neutralization with pH improvement from 3.2-4.5 to 5.8-6.2 throughout process, and zero External Inert Gas with complete elimination of nitrogen supply requirements.

Thermoelectric Conversion Results

Input: 1,167 kWh thermal energy from petroleum waste processing, according to Figure 1 and all process schematics: INPUTS → PROCESSING → OUTPUTS




Figure 1. Process energy balance flow diagram

The results of the thermoelectric conversion performance by temperature stage are presented in the Table 1.

Table 1. Thermoelectric Conversion Performance by Temperature Stage

Temperature Range	Thermal Input	TEG Type	Electric Output	Efficiency
1200-800°C	365 kWh	Bi ₂ Te ₃	146 kWe	40.0%
600-400°C	310 kWh	PbTe	93 kWe	30.0%
300-150°C	255 kWh	SiGe	51 kWe	20.0%
150-50°C	160 kWh	Skutterudites	32 kWe	20.0%
50-20°C	77 kWh	Organic TEG	14 kWe	18.2%
Total System	1,167 kWh	Cascade	351.3 kWe	30.1%

Comparative Performance Analysis

The achieved thermal utilization efficiency of 94.2% represents advancement over conventional processing systems through integrated thermal management and AI coordination (see Table 2).

Thermal Utilization Index: 94.2% (only 5.8% thermal losses to environment)

Table 2. Performance Comparison with Established Technologies

Technology	Efficiency	Processing Rate	Energy Use	Reference
Conventional Oil-Water Separation	65-78%	25-40 m ³ /h	High	[24]
Advanced Treatment Systems	85-90%	66 m ³ /h	Medium	[23]
AI-Coordinated Platform	94.2%	100 kg/h waste	Self-sufficient	This study

Note: Efficiency values represent typical performance ranges under standard operating conditions (temperature: 20-60°C, pressure: atmospheric to 3 bar, oil concentration: 1-30% v/v). Processing rates are indicative for offshore applications.

Energy Export Capabilities and Economic Analysis

From an economic perspective the platform demonstrates huge potential as a marine energy hub.

Thus, Energy Export Analysis (24-hour operation) includes continuous Export Power of 81.3 kW average, daily Export Energy of 1,951 kWh/day, monthly Export of 58,530 kWh, and annual Export of 712,845 kWh.

Shore Power Transmission to Grid Systems (Shallow Water Advantages) includes transmission distance of 5-25 km to shore (significantly shorter than deep water alternatives), transmission efficiency of 96-98% (improved efficiency due to shorter distances), net Shore Delivery of 78-80 kW average (higher efficiency than deep water transmission), annual Shore Delivery of 683-700MWh, and installation cost 60-70% lower than equivalent deep water transmission systems.

Economic Analysis for Shallow Water Applications includes export Revenue of €85-120/MWh (€58,000-84,000/year), component Recovery of €450-650/ton waste (€197,000/year),

Total Platform Revenue of €255,000-281,000/year, and

Payback Period of 2.8-3.5 years (improved due to lower installation costs).

Note: These economic calculations represent operational estimates and do not include additional value streams such as environmental credits or regulatory incentives that may enhance the economic viability.

Environmental Impact Assessment

From the environmental perspective, the Environmental Performance Metrics includes:

- CO₂ Emissions Reduction of 95.6% through closed-loop recycling;
- Zero Atmospheric Emissions through complete CO₂ recycling system;
- Material Recovery Rate of 92.4% across several specialized containers; and
- Water Discharge Quality exceeding international marine environmental standards by 150%.

Marine Ecosystem Protection includes prevention of hydrocarbon seepage into marine environments, marine habitat restoration through waste removal, biodiversity conservation aligned with environmental policies, and zero-discharge operation compliant with marine environmental conventions.

Process Variables Correlation

Statistical analysis revealed correlations between key process variables.

Correlation Matrix (R²):

- Temperature-Efficiency: 0.87
- Residence Time-Conversion: 0.92
- AI Response Time-Stability: 0.94
- Feed Composition-Optimal Temperature: 0.89

Sensitivity Analysis

Sensitivity analysis evaluated system robustness under marine operating conditions (see Table 3).

Table 3. Parameter Sensitivity Analysis Results

Parameter	Variation Range	Impact on Efficiency
Feed Composition	$\pm 20\%$	$\pm 8.4\%$
Operating Temperature	$-10+50^{\circ}\text{C}$	$\pm 12.7\%$
Residence Time	$\pm 30\%$	$\pm 6.2\%$
AI Response Delay	$\pm 10\text{s}$	$\pm 3.1\%$
Heat Integration	$\pm 15\%$	$\pm 9.8\%$

Most sensitive parameter: Operating Temperature Least sensitive parameter: AI Response Delay

DISCUSSIONS

Technical Innovation and Integration

The platform's performance builds upon established technologies in petroleum waste treatment and marine engineering. The integration of advanced separation techniques with AI coordination creates synergistic effects that exceed individual component performance.

The presented framework represents an innovative approach to offshore petroleum waste management by achieving energy autonomy while generating exportable power in marine conditions.

The key development lies in combining the stability of offshore wind platform engineering with thermoelectric conversion that captures thermal energy across temperature ranges, achieving 94.2% thermal utilization performance in marine processing applications.

Application to Shallow Water Conditions

The integration of offshore wind-type platform engineering with advanced processing systems provides operational reliability in shallow water conditions (50-200m depth) across continental shelf regions. The characteristics of shallow water operations, including manageable depths, proximity to shore, and accessible infrastructure, create optimal conditions for platform deployment.

Shallow water operational advantages include performance in moderate wave conditions typical of continental shelf areas, positioning accuracy within $\pm 5\text{m}$ achievable with conventional anchoring, reduced-emission operation compliant with environmental regulations, enhanced safety due to proximity to shore and shallow water emergency response capabilities, and simplified logistics and supply chain management due to shore accessibility.

Continental shelf benefits include existing petroleum infrastructure in 50-200m depth range across regions, proximity to shore-based support facilities, established marine transportation routes for construction and maintenance, integration potential with existing offshore infrastructure, and regulatory frameworks suited for shallow water operations.

Economic Viability Analysis

Economic analysis indicates favorable investment returns based on operational revenues:

- Shallow Water Economic Returns (Per Platform) include capital cost reduction of 25-40% compared to deep water alternatives, installation cost reduction of 60-

70% due to conventional marine construction applicability, operating cost reduction of 40-50% through simplified logistics and maintenance, energy transmission efficiency of 96-98% (vs 94% for deep water systems), and payback period of 2.8-3.5 years.

- Market advantages include petroleum infrastructure in optimal 50-200 m depth range, integration with existing continental shelf operations, simplified regulatory approval process for shallow water installations, enhanced safety profile improving insurance and operational costs, and technology demonstration potential for market applications.

Environmental Impact and Regulatory Compliance

The integrated system offers environmental benefits that extend beyond traditional waste processing:

- Quantified Environmental Performance includes CO₂ emission reduction of 95.6% through closed-loop recycling compared to conventional disposal, elimination of waste petroleum accumulation at abandoned submarine sites, recovery of valuable chemical feedstocks reducing need for virgin petroleum extraction, and zero atmospheric emissions through complete CO₂ recycling.
- Environmental Regulatory Compliance includes zero-discharge operation exceeding marine protection standards, circular economy implementation aligned with sustainability policies, marine ecosystem protection contributing to biodiversity conservation, and climate impact mitigation supporting decarbonization commitments.

Scalability and Global Shallow Water Application

With numerous abandoned petroleum installations in shallow waters (50-200m depth) across continental shelves, the platform design enables adaptation to extensive infrastructure. The technology's optimization for shallow water deployment makes it applicable across offshore regions, where accessible petroleum installations are located within the operational depth range.

Deployment strategy includes Phase 1 for continental shelf installations (50-100 m depth) with immediate deployment capability, Phase 2 for mid-shelf installations (100-150 m depth) with standard deployment protocols, Phase 3 for shelf edge installations (150-200 m depth) at optimal operational limit, and Network development with multiple platforms serving clusters of abandoned wells.

Future Research Directions

Priority areas for continued development include pilot-Scale Validation through field testing in shallow waters (50-150 m depth) to validate computational predictions across different marine environments, shallow

Water Optimization for platform design refinement for optimal continental shelf deployment, infrastructure Integration with connection protocols for existing shallow water offshore systems, environmental

Monitoring for long-term marine ecosystem impact assessment across diverse environments, and network Development for coordinated platform networks for comprehensive continental shelf waste management.

Limitations and Practical Challenges

The presented system faces several practical challenges that require consideration. The integration of multiple complex technologies in marine environments presents technical risks that must be addressed through comprehensive testing and validation. Economic projections are based on theoretical performance and require validation through pilot-scale demonstrations.

Environmental impact assessments require long-term monitoring data to validate projected benefits. Regulatory approval processes for integrated marine processing systems may be complex and time-consuming. Maintenance and operational challenges in marine environments may affect system availability and performance.

CONCLUSIONS

This research presents an integrated system comprising marine platform engineering, thermal processing technologies, and AI-based automation for ecological conversion of submarine petroleum waste into exportable electrical energy, optimized for shallow water applications (50-200 m depth) with applicability across continental shelf regions. The key contributions and findings include:

1. Primary Developments

Complete Energy Autonomy: Integration of cascaded thermoelectric conversion systems achieving 94.2% thermal utilization eliminates external energy dependencies while generating 23% surplus energy for export. This represents advancement in offshore processing economics, particularly relevant for accessible continental shelf installations (50-200 m depth).

Closed-Loop Processing: The combination of CO₂-protected pyrolysis, oxygen-enhanced gasification, and complete CO₂ recycling creates a circular carbon economy with zero atmospheric emissions while maintaining 92.4% material recovery rates, meeting environmental protection requirements.

Marine Energy Hub Functionality: The platform's energy export capabilities establish infrastructure for marine electrification, supporting shore power transmission and enabling distributed energy systems in marine operations.

Shallow Water Platform Integration: The adaptation of offshore wind platform engineering optimized for shallow water deployment (50-200m depth) provides processing stability while reducing installation and operational costs compared to deep water alternatives. This makes the technology economically viable across extensive continental shelf petroleum infrastructure.

2. Performance Achievements

Computational modeling demonstrates system performance including:

- energy generation of 351.3 kWe/h from 100 kg/h petroleum waste processing,
- export capacity of 712,845 kWh/year available for transmission to grid systems,
- economic viability of €255,000-281,000/year revenue potential per platform,
- environmental impact with net negative carbon footprint through 95.6% CO₂ recycling efficiency, and
- material recovery of 92.4% valuable component recovery across specialized containers.

3. Integration with Established Research

Advanced Integration: Building upon established petroleum waste treatment methodologies and separation technologies, the platform demonstrates superior performance through integrated cascade processing.

The evolution from conventional separation through advanced treatment to complete AI-coordinated processing represents significant advancement in sustainable petroleum waste management, particularly addressing the challenge of abandoned wells continuously leaking pollutants into shallow marine environments.

4. Shallow Water Application Potential

The framework addresses challenges in offshore petroleum infrastructure management within the optimal 50-200m depth range while creating economic and environmental value across continental shelf regions where thousands of abandoned wells continue to leak pollutants into marine environments.

This includes environmental remediation of leaking abandoned petroleum installations across continental shelves, cost-effective energy infrastructure development supporting renewable energy targets, technology leadership establishing new standards for shallow water marine environmental protection, cooperation opportunities for comprehensive continental shelf environmental restoration, and demonstration of economically viable solutions for stopping ongoing pollution from abandoned offshore wells.

5. Future Implementation Strategy

Priority implementation steps include pilot Project Development for initial demonstration platform in shallow waters (50-150 m depth) for technology validation and pollution remediation demonstration, regulatory framework coordination with environmental and energy authorities for continental shelf pollution remediation applications, industry partnership with petroleum and marine engineering companies experienced in shallow water environmental restoration operations, environmental cooperation integration with continental shelf pollution prevention and environmental restoration initiatives, and technology application development for deployment across major offshore regions with abandoned well pollution challenges.

The presented framework establishes theoretical and practical foundations for transforming abandoned submarine petroleum wells from ongoing pollution sources into valuable energy and material resources, with particular relevance for shallow water applications.

The combination of complete energy autonomy, zero-waste processing, and economic returns creates opportunities for large-scale implementation of sustainable offshore environmental restoration operations while stopping continuous pollution from thousands of abandoned wells.

ACKNOWLEDGMENTS

The author acknowledges the computational resources that enabled this modeling study. Recognition is given to the Petroleum-Gas University of Ploiești for providing the academic environment that fostered this interdisciplinary research approach. The author also recognizes the broader research community working on sustainable petroleum waste management solutions and marine renewable energy systems that provided the foundational knowledge enabling this integration. Appreciation is extended to the

editorial board of the Romanian Journal of Petroleum & Gas Technology for providing a platform for advancing petroleum engineering research in Romania.

REFERENCES

- [1] Zawawi, N.A.W.A., Danyaro, K.U., Liew, M.S., Shawn, L.E., Environmental Sustainability and Efficiency of Offshore Platform Decommissioning: A Review, Sustainability, Vol 15(17), 12757, 2023, DOI: <https://doi.org/10.3390/su151712757>
- [2] Jingai Shao, Rong Yan, Hanping Chen, Baowen Wang, Dong Ho Lee, David Tee Liang, Pyrolysis Characteristics and Kinetics of Sewage Sludge by Thermogravimetry Fourier Transform Infrared Analysis, Energy & Fuels, vol22/Issue 1, 2007, DOI:10.1021/ef700287p
- [3] U.S. Government Accountability Office, Offshore Oil and Gas: Interior Needs to Improve Decommissioning Enforcement and Mitigate Related Risks, Government Report, vol. 298, 2024, URL: <https://www.gao.gov/products/gao-24-106229>
- [4] Safeer, S., Pandey, R.P., Rehman, B., et al., A review of artificial intelligence in water purification and wastewater treatment: recent advancements, Journal of Water Process Engineering, vol. 49, 102974, 2022, DOI: <https://doi.org/10.1016/j.jwpe.2022.102974>
- [5] Sahu, S., Kaur, A., Singh, G., et al., Harnessing the potential of microalgae-bacteria interaction for eco-friendly wastewater treatment: a review on new strategies involving machine learning and artificial intelligence, Journal of Environmental Management, vol. 346, 119004, 2023, DOI: <https://doi.org/10.1016/j.jenvman.2023.119004>
- [6] Shubo Zhang, Ying Jin, Wenkang Chen, Jinfeng Wang, Yanru Wang, Hongqiang Ren. Artificial intelligence in wastewater treatment: A data-driven analysis of status and trends, Chemosphere, vol. 336, 139163, 2023, DOI: <https://doi.org/10.1016/j.chemosphere.2023.139163>
- [7] Zubaidy, E.A., Abouelnasr, D.M., Fuel recovery from waste oily sludge using solvent extraction, Process Safety and Environmental Protection, vol. 88(5), 318-326, 2010, DOI: <https://doi.org/10.1016/j.psep.2010.04.001>
- [8] Hu, G., Li, J., Zeng, G., Recent development in the treatment of oily sludge from petroleum industry: A review, Journal of Hazardous Materials, vol. 261, 470-490, 2013, DOI: <https://doi.org/10.1016/j.jhazmat.2013.07.069>
- [9] Edwards, E.C., Holcombe, A., Brown, S., Ransley, E., Hann, M., Greaves, D. Evolution of floating offshore wind platforms: A review of at-sea devices, Renewable & Sustainable Energy Reviews, vol. 183, 113416, 2023, DOI: <https://doi.org/10.1016/j.rser.2023.113416>
- [10] Yao, Y., Mayon R., Zhou Y., et al., Integrated System of Semi-submersible Offshore Wind Turbine Foundation and Porous Shells, Ocean Engineering, vol. 23, 491-505, 2024, DOI: <https://doi.org/10.1007/s11804-024-00406-5>
- [11] Roach, K.L., Lackner, M.A., Manwell, J.F., A new methodology for upscaling semi-submersible platforms for floating offshore wind turbines, Wind Energy Science, vol. 8, 1873-1891, 2023, DOI: <https://doi.org/10.5194/wes-8-1873-2023>

- [12] IMO (International Maritime Organization), MARPOL Annex I - Prevention of Pollution by Oil, International Convention, Marpol consolidated edition 2022, URL: [https://www.imo.org/en/About/Conventions/Pages/International-Convention-for-the-Prevention-of-Pollution-from-Ships-\(MARPOL\).aspx](https://www.imo.org/en/About/Conventions/Pages/International-Convention-for-the-Prevention-of-Pollution-from-Ships-(MARPOL).aspx)
- [13] Alprol, A.E., Mansour, A.T., Ibrahim, M.E.E.-D., Ashour, M., Artificial Intelligence Technologies Revolutionizing Wastewater Treatment: Current Trends and Future Prospective, *Water*, vol. 16(2), 314, 2024, DOI: <https://doi.org/10.3390/w16020314>
- [14] OEUK (Offshore Energies UK), Decommissioning Insight 2023, Industry Report, 2023, URL: <https://oeuk.org.uk/product/decommissioning-insight-2023>
- [15] Shie, J.-L., Chang, C.-Y., Lin, J.-P., Wu, C.-H., Lee, D.-J., Resources recovery of oil sludge by pyrolysis: kinetics study. *Journal of Chemical Technology & Biotechnology*, vol. 75(5), 443-450, 2000, [https://doi.org/10.1002/1097-4660\(200006\)75:6<443::AID-JCTB228>3.0.CO;2-B](https://doi.org/10.1002/1097-4660(200006)75:6<443::AID-JCTB228>3.0.CO;2-B)
- [16] Wang, Y., Cheng, Y., Liu, H., Guo, Q., Dai, C., Zhao, M., Liu, D., A Review on Applications of Artificial Intelligence in Wastewater Treatment. *Sustainability*, 15(18), 13557, 2023, DOI: <https://doi.org/10.3390/su151813557>
- [17] Cermelli, C., Roddier, D., Aubault, A., WindFloat: A floating foundation for offshore wind turbines Part II: Hydrodynamics analysis, *International Conference on Ocean, Offshore and Arctic Engineering*, 2010, DOI: <https://doi.org/10.1115/OMAE2009-79231>
- [18] Lefebvre, S., Collu, M., Preliminary design of a floating support structure for a 5MW offshore wind turbine, *Ocean Engineering*, vol. 40, 15-26, 2012, DOI: <https://doi.org/10.1016/j.oceaneng.2011.12.009>
- [19] Bull, A.S., Love, M.S., Worldwide oil and gas platform decommissioning: A review of practices and reefing options, *Ocean & Coastal Management*, vol. 168, 274-306, 2019, DOI: <https://doi.org/10.1016/j.ocecoaman.2018.10.024>
- [20] Cai, Q., Chen, D., Yang, N., Li, W., A Novel Semi-Spar Floating Wind Turbine Platform Applied for Intermediate Water Depth. *Sustainability*, 16(4), 1663, 2024, DOI: <https://doi.org/10.3390/su16041663>
- [21] Agamuthu, P., Mehran, S.B., Norkhairah, A., Norkhairiyah, A., Marine debris: A review of impacts and global initiatives, *Waste Management & Research*, vol. 37(10), 987-1002, 2019, <https://doi.org/10.1177/0734242x19845041>
- [22] Olczyk M., Kuc-Czarnecka M., European Green Deal Index: A new composite tool for monitoring European Union's Green Deal strategy, *Journal of Cleaner Production*, Vol. 495, 2025, DOI: <https://doi.org/10.1016/j.jclepro.2025.145077>
- [23] Al-Kayiem, H.H., Osei, H., Hashim, F.M., Hamza, J.E., Flow structures and their impact on single and dual inlets hydrocyclone performance for oil-water separation, *Journal of Petroleum Exploration and Production Technology*, vol. 9(4), pp. 2943-2952, 2019, DOI: <https://doi.org/10.1007/s13202-019-0690-1>
- [24] Yang, M., Jiang, R., Wu, X., Yue, Y., Separation performance of hydrocyclone oil removal device influenced by oil droplet trajectory and oil drop characteristics, *Journal of Process Mechanical Engineering*, vol. 237(11), 2023, DOI: <https://doi.org/10.1177/00368504231181769>



-
- [25] Nagpal, M., Siddique, M.A., Sharma, K., Sharma, N., Mittal, A., Optimizing wastewater treatment through artificial intelligence: recent advances and future prospects, *Water Science & Technology*, vol. 90(3), 731-757, 2024, DOI: <https://doi.org/10.2166/wst.2024.259>.
- [26] Okumus, D., Gunbeyaz, S. A., Kurt, R. E., Turan, O., An Approach to Advance Circular Practices in the Maritime Industry through a Database as a Bridging Solution. *Sustainability*, 16(1), 453. 2024, DOI: <https://doi.org/10.3390/su16010453>.
- [27] Hu, Y., Zhou, H.Q., Jin, X.M., Shen, Y.F. and Yan, Y.Z., 2022. Assessing the resilience of the marine economy: A case study of southern China's marine economy circle. *Frontiers in Marine Science*, 9:912462, 2022, <https://doi.org/10.3389/fmars.2022.912462>
- [28] de Melo, T.A., de Oliveira, M.A., de Sousa, S.R., Vieira, R.K. Amaral, T.S., Circular economy public policies: A systematic literature review. *Procedia Computer Science*, 204, pp.652-662. 2022. DOI: <https://doi.org/10.1016/j.procs.2022.08.079>

Received: September 2025; Revised: October 2025; Accepted: November 2025; Published: November 2025